

3516 PolySOL™ Pop-Up Film Satin 12 mil

PRODUCT DESCRIPTION

3516 PolySOL™ Pop-Up Film is a 12mil polyester display film with a "low glare" satin finish and an instant dry, water resistant coating. The durable 12mil construction is intended to be used unlaminated to create a durable tradeshow panel engineered to withstand repeated rolling in portable display units without cupping, warping or scratching. For additional protection 3516 can be overlaminated with both pressure sensitive and hot laminates



ADVANTAGES

- Stiff Polyester Base
- Low Glare Satin Finish
- >99% Opacity / Blockout
- Instant Dry / Water Resistant
- Lay Flat / Will Not "Cup" Over Time

TECHNOLOGIES



(soL) Solvent



Latex

APPLICATIONS

- Durable Tear Resistant Roll-Ups where Blockout is Needed
- Travelling Seminars, Recruitment Sessions, Training Events

PHYSICAL PROPERTIES

| Caliper | 12 mil | |
|--------------|----------|--|
| Basis Weight | 420 g/m² | |
| Gloss (60°) | 16 | |
| Opacity | >99% | |

^{*}All values listed are target values

ADDITIONAL INFORMATION

- Available widths: 36"/54" 3" core
- For additional product information please call 1-800-366-7393 or visit our website www.sihlinc.com where you can also find an authorized Sihl reseller near you.